



# WARM AIR HAND DRYERS

## SL-2008 Series

**NEW**



SL-2008

Activated by means of a push button.  
Run-On-Time of 45 seconds.  
Polycarbonate casing.

S&P warm air hand dryers protected against vertical water splash.  
Fitted with thermal overload protection in the motor and the heating element.  
Motor Class II.



SL-2008 A SILVER



SL-2008 AUTOMATIC

Automatic activation by means of an infrared sensor.  
The unit is switched off when the hands are removed.  
Polycarbonate casing.  
Security device to avoid continued function if exhaust is blocked.

### ■ Technical characteristics

Model	Maximum power absorbed (W)	Voltage (V) 50 Hz	Maximum airflow (m <sup>3</sup> /h)	Sound pressure level (dB(A))	Weight (kg)	Dimensions LxAxH (mm)	Casing material	On	Off	Colour
SL-2008	1875	230	170	52	2,8	212x155x332	Polycarbonate	Push button	Run-On-Timer 45s	White
SL-2008 AUTOMATIC	1875	230	170	52	2,8	212x155x332	Polycarbonate	Infra-red	When the hands are removed	White
SL-2008 A SILVER	1875	230	170	52	2,8	212x155x332	Polycarbonate	Infra-red	When the hands are removed	Silver

